

## **FURNACE - DIESEL FIRED**

## 27 kW



This compact indirect-fired diesel unit is ideal for smaller heating projects. Well equipped for remote locations, these units require a diesel fuel source and 115 volt power for the supply fan. Compact size and light weight allows for easy portability. Designed to sit outside with the supply air ducted inside, these units can also be positioned inside with the combustion gas ducted to the exterior.

#### Features:

- · Large scale clean, dry heat
- Industrial grade power burner, stainless steel heat exchanger
- Vented combustion gases allow for safe use in confined areas

#### **Applications:**

- Temporary Structures
- Industrial Plants
- Construction



Small scale construction heating projects are a perfect match for this specialized heating unit. Separate combustion air allows for high temperature supply air but with a low humidity level. Dry air enables moisture trapped in construction materials to be released resulting in a drier project.



This "western town" film set had no builtin heating system. These versatile 27 kW diesel-fired units proved to be very dependable and provided just the right amount of heat. Clean, warm air was appreciated by both cast and crew.



This steel storage building is utilized once a year for a large formal dinner/dance. The dedicated heating units didn't have sufficient heating strength when the evening festivities required suit, tie and formal dresses. The large heater from Cool Air provided the horsepower to get the temperature to comfortable levels while the quieter 27 kW unit kept the level maintained.

# FURNACE - DIESEL FIRED **27 kW** (HOF27H11)

HEATING	27 kW	PHYSICAL	27 kW	
Medium	Diesel Fired	Controls	Local ON/OFF,	
Capacity	90,273 BTU		Remote thermostat	
Capacity	27 kW	Supply Air Flow	1021 CFM	
		Flexible Ducting	12" up to 25'	
		Fuel Tank Capacity	17.2 US Gal	66 L
ELECTRICAL		Consumption - Diesel	0.8 US Gal/hr	3.07 L/hr
Voltage	115	Run Time	21 hours	
Phase	Single	Heat Rise	162° F	72° C
Breaker Size	15 Amps	Static Pressure	0.5"	
Current Draw	12 Amps	Flue Connection	6"	
Plug	NEMA 5-15P	Wheel Type	10" flat-free	
Power Cord Length	1'	Dimensions - Width	24"	61 cm
Power Cord Wire Size	14/3	Dimensions - Depth	48"	122 cm
		Dimensions - Height	34"	87 cm
		Weight w/ fuel	248 lbs	113 kg



Large flat-free tires and balanced construction allow this large unit to be wheeled with relative ease.



High heat insulated duct with pin lock connections can be easily coupled to customize any installation.



A selective toggle allows you to go from on/off control to a wired remote thermostat.

We also rent industrial and portable air conditioning units, fans, and air movers.

Visit www.cool-air.com for our full line of rental equipment.

### **COOL AIR RENTALS LTD.**

1407 East Georgia St Vancouver, BC Canada V5L 2A9 9531 42 Ave NW Edmonton, AB Canada T6E 5Y4 Tel: 604.253.4171

Toll Free: 1.855.253.4171

cool-air.com

Email: info@cool-air.com

