

HOOK IT UP WCI10V23

THIS IS A QUICK INSTALL GUIDE - ENSURE ALL WORK IS DONE BY QUALIFIED PERSONNEL



- · Place indoors ONLY.
- Locate on level surface with wheels locked.
- Allow 8" clearance on all sides for proper air flow.



- · Must conform to Electrical Code.
- Equipped with 2' Cam-Lok cord ends.
- Incorrect phasing indicated by warning light.



- Ductable up to 75'
- Straight- eliminate bunching and hard turns on duct run
- 90'- can pressurize server room floor
- Square- adjust air delivery with louvers



- Water supply must be capable of 7 gpm.
- · Janitors sink will work.
- Cool air can supply the necessary connection hardware.
- Dual check valve available upon request.



- Supply: 3/4" BLUE PVC hose ONLY.
- Return: 3/4" BLACK RUBBER hose ONLY.
- Hand tighten DO NOT use wrenches.
- DO NOT operate unit without supply water turned on.



- Use 3/8" clear braided water tubing.
- \bullet Use two wrenches to secure this tubing.
- Carefully lay and secure condensate to BLACK return hose.
- Secure both hoses to drain assembly.



- Thermostat control temperature.
- Push-Button simple ON/OFF Switch.
- Remote Control from 10' to 100' away.
- Please obtain operating instructions for complete details.



- DO NOT run without filters in place.
- Inspect filters weekly and clean and/or replace as required.
- To clean vacuum and/or wash.



- These are complex machines.
- Please follow instructions closely for safety and reliability.
- Call Cool Air at any time for more information on installation or operation.