



COOL AIR™
RENTALS LTD

AIR COOLED EMERGENCY RESPONSE UNIT with ELECTRIC HEAT

5 TON



Built to military specifications, this unit is the upmost in mobility and durability. Able to heat and cool, this 5 ton unit is ideal for applications where you need to heat in the morning and afternoon, yet be able to cool once the sun comes out in the middle of the day. Fly it in... oh yeah, it has hooks specifically for that built in. Get the chopper warmed up!

Features:

- Electric elements allow this unit to heat when required
- Easy to understand controls ensure fool-proof field operation
- Weatherproof military-grade construction

Applications:

- Emergency Cooling & Heating
- Temporary Structures
- Disaster Relief



An area within this studio needed spot cooling. That's where this 5 ton is a great fit. While it lacks the cooling strength to cool an entire stage, this unit has plenty of push to cool specific sets.



There was no air conditioning in this care facility. Staff and residents were looking at re-locating as conditions were getting unbearable. Our unit provided the cooling they needed, and indoor conditions were kept at acceptable levels.



When the heat of summer came, it was apparent that this building's cooling couldn't keep up. Rather than risk losing customers or employees to sweltering conditions, this smart business owner brought in a Cool Air unit to ensure everyone was comfortable and that sales could flourish.

REAL COOL. REAL FAST.

AIR COOLED INDUSTRIAL UNIT with ELECTRIC HEAT

ACI5H23ER

COOLING		PHYSICAL	
Medium	Air	Controls	Local or Wired Remote Thermostat
Capacity (Btu)	60,000	Control Connection	MS2102R-16S1S on 50'
Capacity (Ton)	5	Evaporator Air Flow	2000 CFM
HEATING		Supply Air Duct	1-16" x 75' max
Medium	Electric	Return Air Duct	1-16" x 10' max
Capacity (Btu)	37,000	Condensation Collection	Gravity - 25' x 3/4" hose supplied
Capacity (KW)	11	Filter Type	Permanent Washable
ELECTRICAL		Filter Size	29.5" x 22.25" x 0.5"
(Two energy options, both supplied)		Caster Type	Dual 10" Flat-free Swivel
Voltage	208 V	Dimensions - W	43.5" 111 cm
Phase	Three	Dimensions - D	53" 135 cm
Breaker Size	50	Dimensions - H w/o casters	55" 140cm
Cooling Current Draw	29.5 FLA	Dimensions - H w/ casters	69" 175cm
Heating Current Draw	35 FLA	Weight	895 lbs 406 kg
Plug - Cool Air Adapter	Cam-Lok		
Power Cord Length	2'		
Power Cord Wire Size	#2 AWG Sgl. Conductor C-Way		
Plug - Factory Option	MS31032R32-22P		
Power Cord Length	30' Connector X Bare End		
Power Cord Wire Size	#8 AWG 4 Conductor		



ROLL IN

Housed in an aluminum frame, this unit can be moved into position by forklift, crane or just by rolling.



PLUG IN

Large, flexible duct runs carry frosty air to wherever it's needed.



TURN ON

Well-labelled and easy to use rotary dials allow you to operate this unit without in-depth instruction.

We also rent hydronic, electric and indirect fired heaters, ventilation units, and pumps. Visit www.cool-air.com for our full line of rental equipment.

Vancouver

604.253.4171

Kelowna

236.788.4354

Edmonton

825.535.3362

Calgary

403.472.2918

Online

www.cool-air.com
info@cool-air.com

